



Used when high accuracy of machining is needed.
For use on lathes, rotary tables, indexing heads, etc.

Standard accessories:

- 1 set of hard sectional jaws (master+hard top reversible)
- 1 wrench
- 1 set of mounting screws.

Optional accessories:

- 1 set of soft top jaws
- 1 set of outside hard solid jaws
- 1 set of inside hard solid jaws

三爪自定心卡盘用于高精度的加工过程。

标准配件:



- 一套分离爪
- 一个扳手
- 一套螺丝

可选配件:

- 一套软上爪
- 一套上爪
- 一套滑座



K11 SERIES THREE-JAW SELF-CENTERING CHUCKS(2-PIECE JAW) K11 三自定心卡盘 (分离爪)



前锁 FRONT MOUNTING

SPECIFICATIONS

UNIT:mm

chuck size	D1	D2	D3	H	H1	H2	h	z-d	NM Max.input torque	R.P.M Max.speed	Kg Net wt.	Code No
125	95	108	30	95	58	63.0	4	3-M8	100	3000	4.8	K11-125A
130	100	115	30	97	60	65.0	5	3-M8	100	3000	4.3	K11-130A
160	130	142	45	109	65	71.0	5	3-M8	160	2500	8.3	K11-160A
190	155	172	55	122	75	78.0	5	3-M10	250	2000	9.5	K11-190A
200	165	180	65	122	75	78.0	5	3-M10	250	2000	13.0	K11-200A
230	190	210	70	136	80	84.0	6	3-M12	250	2000	14.5	K11-230A
240	195	215	70	136	80	84.0	8	3-M12	320	1600	22.5	K11-240A
250	206	226	80	136	80	86.0	5	3-M12	320	1600	23.0	K11-250A
315	260	285	100	156.5	90	99.5	6	3-M16	400	1200	41	K11-315A
320	270	290	100	156.5	90	99.5	6	3-M16	400	1200	42	K11-320A
325	272	296	100	156.5	90	99.5	6	3-M16	400	1200	41	K11-325A
380	325	350	135	173.5	98	107.5	6	3-M16	500	1000	46	K11-380A
400	340	368	130	173.5	100	112.5	6	3-M16	500	1000	62	K11-400A
500	440	465	210	202.0	115	126.0	6	6-M16	630	800	71	K11-500A
630	560	595	270	220.5	135	144.5	7	6-M16	800	800	200	K11-630A